

# PRODUCT DATA SHEET

## llio white 3000K



### DESIGN BY:

Ernesto Gismondi 2013

#### MATERIALS:

Aluminium, steel

## DESCRIPTION:

With simple geometry, stripped of all formal digressions and reduced to its basics, Ilio draws attention through saturated colour, available in 7 variations. A mono-material aluminium cylinder supports a 39W LED optical engine on the top, which produces high-efficiency diffused indirect light emissions. With a flow of more than 2700 lumen and an 80% yield, it ensures the general lighting of a room. With light regulator configured to controlled socket, dimmer microswitch.



Light emission



Dimmable +0-

#### TECHNICAL DATA SHEET

Product name:
Article Code:
Colour:
Material:
Series:
Environment:
Area contract:

#### OPTICS

Emission:

#### DIMENSIONS

Height:	cm 175
Diameter:	cm 9
Base Length:	cm 30
Base Width:	cm 30
Impact Resistance:	N.D.
Glow Wire Test:	750 °

#### LAMPS INCLUDED

Category:	LED COB
Number:	1
Watt:	45W
Luminous Flux (Im):	4230lm
Color temperature (K):	3000K
Class:	A

#### LUMINAIR

Watt:
Luminous Flux (Im):
CCT:
Efficiency:
Efficacy:
CRI:
Dimmer
Dimmable

llio white 3000K 1640020A White Aluminium, steel Design Indoor Hospitality Hotel, Hospitality Restaurant, Private Residence

Indirect

45W 3564lm 3000K 88% 83lm/W 90



® 90

DIMENSIONS

