

# PRODUCT DATA SHEET

# Ilio Blue electro 3000K



### **DESIGN BY:**

Ernesto Gismondi 2013

#### MATERIALS:

Aluminium, steel

### **DESCRIPTION:**

With simple geometry, stripped of all formal digressions and reduced to its basics, Ilio draws attention through saturated colour, available in 7 variations. A mono-material aluminium cylinder supports a 39W LED optical engine on the top, which produces high-efficiency diffused indirect light emissions. With a flow of more than 2700 lumen and an 80% yield, it ensures the general lighting of a room. With light regulator configured to controlled socket, dimmer microswitch.



Light emission



# Dimmable +0-

#### TECHNICAL DATA SHEET

| FEATURES  |   | DIMENSIONS |
|---|---|------------|
| Product name:<br>Article Code:<br>Colour:<br>Material:<br>Series: | llio Blue electro 3000K<br>1640050A<br>Blue electro<br>Aluminium, steel<br>Design | 09 Ø       |
| Environment:<br>Area contract:                                    | Indoor<br>Hospitality Hotel, Hospitality<br>Restaurant, Private<br>Residence      |            |
| OPTICS  |   |            |

Indirect

cm 175 cm 9 cm 30 cm 30 N.D.

750 °

45W 3564lm 3000K 88% 83lm/W 90

Emission:

# DIMENSIONS

| Height:            |  |
|--------------------|--|
| Diameter:          |  |
| Base Length:       |  |
| Base Width:        |  |
| Impact Resistance: |  |
| Glow Wire Test:    |  |
|                    |  |

## LAMPS INCLUDED

| Category:              | LED COB |
|------------------------|---------|
| Number:                | 1       |
| Watt:                  | 45W     |
| Luminous Flux (Im):    | 4230lm  |
| Color temperature (K): | 3000K   |
| Class:                 | A       |
|                        |         |

#### LUMINAIR

| Watt:               |
|---------------------|
| Luminous Flux (Im): |
| CCT:                |
| Efficiency:         |
| Efficacy:           |
| CRI:                |
| Dimmer              |
| Dimmable            |
|                     |



